BD1000 Dual Voltage Building Dryer BD1000 Single Phase 230v Only Building Dyer

Easy-to-maintain dehumidifier for hire and construction fleets

Remote Monitoring Capability: No

Condensate pump lift capacity: 5.5 m

Condensate Removal: Automatic Pump-out - Centrifugal

Refrigerant Type: R454C

Defrost Type: Reverse Cycle

Average Noise Level: 73.4db

Drain Hose Length: 12.2 M

Power Cord Length: 4.5 M

Wheels: 30cm Semi-pneumatic

Product Warranty: 2 years - limited Refrigeration System Warranty: 6 years

Hosuing Warranty: Rotomoulded Cover - Lifetime

Cable & Hose Storage: Yes

Air Filter: Fibreglass

Handle: Rigid

Stackable: No

Safety Mark: CE

•

•

The BD1000 dehumidifier delivers strong dehumidification performance, durability and reliability within a unique, portable design that withstands the rigours of construction sites and hire. The roto-moulded polyethylene cover is dent resistant, easy to wipe clean, and hinges open for fast access for internal cleaning. Anti-clog design includes double-width coil fin spacing and optional filters to improve performance in dusty environments and reduces cleaning and maintenance costs.

NEW! The BD1000 Dual Voltage now automatically switches between 110v and 230v, depending on the power source. Simplified user controls include rotary on/off switch and manual condensate purge. A flush-mounted hour counter helps plan maintenance schedules and on-board kilowatt-hour meter provides accurate power consumption. Regular, automatic condensate pump-out allows unattended use. A rigid handle, large semi-pneumatic wheels and built-in vehicle loading skids ensures easy transport and maneuverability.

Order codes Dual voltage 123407 Single phase 230v only 126436

DRIEAZ

SPECIFICATION

- Supply Voltage: Dual Voltage 230 / 110V automatically switches or Single phase 230v Only
- Type: Standard Refrigerant
- Water Removal (Max): 48 L / day (32.2°C/90%RH)
- Water Removal (AHAM): 28 L / day (26.7°C/60%RH)
- Water Removal (EU standard): 46 L / day (30°C/80%RH)
- Water Removal (EU standard): 21 L / day (20°C/60%RH)
- Amp Draw: 3.3 Å (230V) 6.5 Å (110V)
- Operating Temperature Range: 5°- 32°C
- Operating Humidity Range: 30 100%
- Dimensions (H × W × D): 85 × 50 × 51 cm
- Use Weight: 50KG
- Air movement: 350 M³/Hr
- Controls: Manual Rotary On/Off
- Hour Counter: Yes
- Killowatt Meter: Yes
- Humidistat: Yes (30-100%)
- Adjustable Defrost Setting: No

4PRO FILTER - ONE filter protects in FOUR ways!

1.Targets smaller particles with a layer of electro-statically charged polypropylene 2.Reduces build-up on internal dehumidifier components by capturing large particles with expanded cellulose mesh

3.Adsorbs odors and fumes with activated carbon

A Antimicrobial-treated filter media

4. Antimicrobial-treated filter media

TRUST LEGEND BRANDS EUROPE TO DELIVER THE BEST!

Unit 56, Tanners Drive, Blakelands Industrial Estate, Milton Keynes. MK14 5BW. Tel: 01908 611211 e-mail: support@legendbrandseurope.com

