



## MXF DCD150-601C KIT

MX FUEL™ 150 MM DIAMOND CORE DRILL

- Core with confidence by delivering AC performance with a maximum core diameter capacity of 152 mm wet & dry
- 2 speed gearing for a wide range of applications, with laser etched speed and capacity markings into the metal body
- Speed 1: up to 75 mm diameter wet & dry coring at 1600 rpm
- Speed 2: 76 to 152 mm diameter wet & dry coring 800 rpm
- Patented AUTOSTOP<sup>™</sup> clutch provides best in class protection, preventing over rotating when losing control or in case of a stuck core
- On-board level sensor guides the user to achieve a straight and accurate finish whilst horizontal drilling
- On-board pressure gauge allows user to optimise drilling speed in order to get the best lifetime of machine and accessory
- On-board battery gauge allows the user to monitor battery capacity during entire drilling process
- Integrated water line for wet coring that is compatible with the M18<sup>™</sup> SWITCH TANK<sup>™</sup> interchangeable sprayer and water supply system
- 1 ¼″ UNC + ½″ G core fitting to fit most common cores, with friction plate design allowing for easy core changes
- Separately available core drill stand MXF DR255TV with 60 mm collar - 60 mm mount on the core drill fits most universal core stands
- ONE-KEY<sup>™</sup> tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY<sup>™</sup> also features a remote locking functionality





					Nc Dri 1s To We (EF	
					Dri	
	$\langle \langle \rangle \rangle = -$				<u>1s</u>	t,
			10 C	6	То	С
and the second of the second s	SA VERSE	1 Milwankee			We	e
	XN			Cidde -	(Ef	þ
		Harris			Sta	
an A						ĥ
- 74/1/10			PIL			
			Y GRAN		Kit	
1 Seller	and a s	N 1 1			Art	1
	LAD SA	N. Dev				ľ
	TRACES					
		The second little				
	Junio -					
Il	T Passa		Var	WEDEN COLUMN		
11		The second of the		State of the second sec		

No load speed (rpm)	0 - 800/ 0 - 1600		
Drilling capacity in concrete 1st/ 2nd gear (mm)	76 - 152/ 25 - 76		
Tool reception	1 ¼″ UNC + ½″ G		
Weight with battery pack (EPTA) (kg)	15.1 (MXF XC406)		
	Trigger lock-on, side handle,		
Standard equipment	MXF DR255TV drill stand		
Standard equipment Kit included			