



Product data sheet

Power tools for trade & industry

Rotary Hammer with SDS plus

GBH 4-32 DFR



Robustness combined with durability and excellent performance in the SDS plus category

The most important data

Rated input power	900 W
Impact energy (according to EPTA 05/2016)	4.2 J
Drilling dia. concrete, hammer drill bits	6 – 32 mm

Part Number 0 611 332 161

Technical data

Performance data

Impact rate at rated speed	0 – 3,600 bpm
----------------------------	---------------

Technical data

Tool holder	SDS plus
Impact energy (according to EPTA 05/2016)	4.2 J
Rated input power	900 W
Packaging dimensions (width x length x height)	353 x 473 x 125 mm
Voltage, electrical	110 V
Weight	4.7 kg
Rated speed	0 – 800 rpm

Drilling range

Drilling dia. concrete, hammer drill bits	6 – 32 mm
Opt. appl. range concrete, hammer drill bits	14 – 25 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	12.7 m/s ²
Uncertainty K	1.5 m/s ²

Chiselling in concrete

Vibration emission value ah	11.4 m/s ²
Uncertainty K	1.5 m/s ²

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- 900 W motor delivers 4.2 J of impact energy for very fast chisel removal rates
- Durable due to robust metal gearbox housing design
- Vibration Control for effortless and continuous work in time-intensive applications

