









PCX 60A PLATE COMPACTOR





FEATURES & BENEFITS

- 11kN high performance Vibrator for maximum compaction and excellent travel speeds.
- Ergonomic operator handle for precise manouverability, includes Pull-Back bar.
- Thickener Plate in rear of Baseplate for increased durability.
- Specially engineered Fabricated Baseplate designed to eradicate 'Track' marks on asphalt.
- Collapsable handle for easy storage and transportation.
- 3 mount HAV system for reduced HAV levels and improved usage time.
- Optional 'Easy-Fit' 12-litre Water Tank & 'Easy-Clean' Spraybar system.
- Durable metallic Water Control Tap for high flow rate.
- Low HAV handles that still allow precision control.
- Optional Integrated 'Quick Engage' Wheel Kit.
- Handle Latch for increased stability whilst operating the Wheel Kit.

TECHNICAL SPECIFICATIONS

Model	PCX 60A		
Part No.	PCU02		
Plate Size (W x L)	(mm)	350 x 400	
Width	(mm)	350	
Length - Operation	(mm)	1010	
Height - Operation	(mm)	1010	
Length - Storage	(mm)	660	
Height - Storage	(mm)	550	
Engine Power	(Hp / kW)	4/3	
*Weight	(kg)	68.5	
Static Pressure	(kg/m^2)	565	
Centrifugal Force	(kN)	11	Options
Frequency	(Hz)	101	OPP/87/DIO
Max. Travel Speed	(m/min)	25	OPP/104/DIO
Max. Gradient	(°)	20	OPP/65/DIO
**Vibration level	(m/sec^2)	4.9	
Noise Level	(dB(A))	105	* Weight does not incl** Vibration levels tes



OPTIONAL 'EASY-FIT' 12LTR
WATER TANK



OPTIONAL INTEGRATED 'QUICK ENGAGE' WHEEL KIT



HANDLE LATCH FOR INCREASED STABILITY WHILST OPERATING THE WHEEL KIT

Detachable Water Kit Integrated Wheel Kit

Paving Pad

* Vibration levels tested to BS5349 using EN 500-4



Weight does not include Water Kit or Wheel Kit.