

PREDATOR DUAL-VOLTAGE OUTPUT BATTERY POWER STATION/BATTERY POWERED GENERATOR

PREDATOR
POWER PRODUCTS



Product Code: PPT048

SPECIFICATIONS

Power Specifications	
Rated output voltage	AC 110V/230V 50 Hz
Socket specification	2*230V 13A UK Sockets, 1* 110V 16A CEE Socket
Rated output power	Max. 3,500 W(AC 230V Ouput)Max. 1.600W(AC 110V Output)
Surge power	Max. 7,000 W or 3,200W
Overload protection	Fuse (34 A or 17 A)
Battery Specifications	
Battery type	Ternary Lithium Ion battery cell
Battery capacity	5,627 Wh
Battery voltage	DC 48 V
Battery cooling	Air (2 x automatic air fans)
Charger Specifications	
Charger voltage	AC 220-240 V 50/60 Hz
Charger output	54.6 V (30 A)
Charging time	± 4.0 hours
Charging cycles	1,500 x (capacity > 80%)
Working Temperatures	
Operating temperature	`-20°C up to 40°C
Charging temperature	0°C up to 30°C
Storage temperature	0°C up to 25°C
Dimensions and Weight	
Dimensions (L x W x H)	583 x 467 x 500 mm
Weight	48 kg
Other	
Ingress protection class	IP21
Warranty	12 months or 300 charging cycles. Whichever comes first.