

Model	EP1650	
Rated output (VA)	1650	
Peak output (VA)	2700	
Capacity (Wh)	1024	
Cell material/connect type	LFP/40135(16S1P)	
AC output	Voltage/frequency	120/60
	THD	≤3%
	Receptacle	2 * American two hole/three pin
USB output	USB-A	3×12 W
	QC3.0	/
	Type-c	2×100 W
DC output	Cigarette lighter	1×12.6V 10A(120W Max)
	5525/5521	2×12V 5A
Charging input	Wall charger/generator	Max 1200W
	Car mounted cigarette lighter	12/24V 8A(Max 96W)
	Solar photovoltaic panels	11V-55V 10A(Max 500W)
Charging time(h)	Wall charger/generator	1.2
	Car mounted cigarette lighter	12
	Solar photovoltaic panels	2.3- 4.5(1×500W)
LED light	Yes(flood LED light)	
Wireless charge	1×15 W	
Bluetooth APP	Yes	
Power Pack&Grid Connection (No Communication Line)	/	
EPS	Yes (less than 20ms)	
Charging/discharging temperature (°C)	0 ~ +40/-20 ~ +40	
LCD display	Energy scale&percentage, input/output power, remaining time of charging/discharging, frequency, usage load flag, fault flag, etc	
Dimension (mm)	337×263×263	
Weight (kg)	12	